

D R Y E N D

Double Backer Drive Roll Rotary Duplex Duplex Stacking



Overview

Unico's Smart Velocity Drive is a digital signal processor (DSP) based variable-speed drive with an embedded software block to control a slitter/scorer. The program offers a number of programmable features that enable OEMs, integrators, and users to customize the functionality of the software to the application.

Features

Modes of Operation

The embedded software has manual and automatic/run modes of operation. In manual mode, the drive can be jogged in both directions. In automatic/run mode, velocity cruise control is enabled and two parallel inputs are used to increase or decrease motor velocity. A third input is used to command the drive to return to a previous speed.

Lineal Tracking

A lineal tracking mode enables the drive to sequence other machine sections based on web tail position, such as during AOC, to start slitter head adjustment, or to initiate rotation of the triplex.

Flexibility and Ease of Use

The software allows the user to easily adjust the velocity and acceleration rates as well as to set up and tune the drive. Fault messages and warning indications are provided for the machine operator. An alphanumeric display shows current drive speed, drive state, and drive status. Analog outputs are available to provide other drives or controls with proportional references of drive speed and/or torque. The drive supports UEdit®, Unico's Windows-based IEC 1131 standard ladder-logic and function-block programming package that provides even greater customization and flexibility. The drive is ideal for retrofits, and seamlessly interfaces into existing logic and with other logic controllers.

Duplex/Triplex Rotate Option

A duplex/triplex rotate option facilitates automatic rotation of the slitter heads into position during automatic-order-change sequence. An additional motor and smart drive are required. When the web is severed, the program tracks the tail and rotates the heads automatically based upon the tracking position. Index and rotate angles are programmable. When the heads are in position, a permissive allows the line to ramp-up speed and resume normal operation.



Smart Slitter/Scorer Drive

Features

Smart AC Digital Drives

(continued)

Unico's 1000 and 2000 drive families provide powerful, flexible digital flux vector control for sophisticated, performance-oriented applications. The drives have been designed for complete flexibility and offer a variety of feedback, programmable I/O, and communication options. They incorporate a number of energy-conserving features, including line regenerative capabilities for exporting energy back to the power grid. Both drive families can take advantage of a modular DC bus configuration for sharing or recirculating energy among multiple drives.

Communication Protocols

The drive supports a variety of serial communication protocols for connecting to virtually any PLC or HMI. The drive can also operate in a stand-alone mode using the built-in keypad/display with an ANSI protocol connection to a simple serial display unit.

- CANopen
- CC-Link
- ControlNet
- DeviceNet
- Ethernet
- Interbus
- Modbus Plus
- Modbus RTU
- Profibus • Remote I/O[†]
- RS-232/422/485

Inputs & **Outputs**

All inputs and outputs are user-enabled and are mapped to hardware I/O points to allow customization of the control. They are also accessible through a highspeed serial communication link.

Inputs

- motor on request
- fault reset
- motion enable
- automatic/run mode
- jog forward
- jog reverse
- increase speed/accel
- decrease speed/decel
- resume speed
- velocity select 0
- velocity select 1
- velocity select 2
- velocity select 3
- tracking start
- blower motor OK

Outputs

- · motor on grant
- no fault
- forward motion
- · reverse motion
- automatic
- manual
- at zero velocity
- at requested velocity
- · at max velocity
- no warning
- motor RMS warning
- thermal warning
- tracking preset

UNICO-Worldwide



All trade designations are provided without reference to the rights of their respective owners.

Specifications subject to

8202 11/06

Corporate **Headquarters**

UNICO, Inc. 3725 Nicholson Road P.O. Box 0505 Franksville, Wisconsin 53126-0505 USA

voice: 262.886.5678 fax: 262.504.7396 www.unicous.com

United States Wixom, Michigan 248.380.7610

New Lenox, Illinois 815.485.5775

Sandy, Utah 801.942.2500 Canada

Mississauga, Ontario 905.602.4677 South America El Tigre, Venezuela 58.283.241.4024

Europe Milton Keynes, England 44.1908.260000 Wilnsdorf, Germany

49.2739.303.0

Asia Osaka, Japan 81.66.945.0077 Beijing, China 86.10.6218.6365

[†]Supported only by the 2000 family platform